

IFP UNILIGHT AR-AFFF TYPE 1/3^{C6}

Alcohol Resistant Aqueous Film Forming Foam Concentrate

DESCRIPTION

IFP UNILIGHT AR-AFFF TYPE 1/3^{C6} is specially formulated non-toxic, viscous foam liquid concentrate, for use in hydrocarbon as well as polar solvent fires. The foam concentrate contains special type of fluorochemical surfactant, hydrocarbon surfactant, solvent, stabilizer, biocide and polysaccharides. It produces aqueous film on hydrocarbon fuel to prevent the fuels vapors come in contact with air and forms a cohesive and regenerative polymeric barrier floats over the alcohol preventing the foam bubble for mixing with polar solvents. IFP UNILIGHT AR-AFFF TYPE 1/3 does not contains any PFOS or PFOA or derivatives

PROPERTIES

Appearance	Light Orange Viscous Liquid
pH	7.0 - 8.0
Specific Gravity	1.00 to 1.04 gm/ml
Viscosity	1500 500 cps
Spreading Co-efficient	More than 3.5
Sludge Contents (% V/V)	Nil
Pour Point	(-) ² °C

APPLICATIONS

IFP UNILIGHT AR-AFFF TYPE 1/3 is intended for use on Class B hydrocarbon fuels such as gasoline, kerosene, diesel etc. at a proportioning rate of 1% and on polar fuels such as alcohols, aldehydes, ketones, ethers, esters etc. at a proportioning rate of 3% with fresh water and salt water. It is applicable with low and medium expansion discharge devices for covering and extinguishing fires of Class A and Class B. IFP UNILIGHT AR-AFFF TYPE 1/3 is suitable for use in special appliances like storage tanks, process areas, warehouses, loading areas, docs and other local risks involving a spilled fuel fire. It is a multipurpose foam and therefore it gives maximum protection against hazards in the fuel storage area irrespective of the type of the fuel.

PROPORTIONING

IFP UNILIGHT AR-AFFF TYPE 1/3 can easily be proportioned using conventional equipments

- Fixed and Portable In-line Inductors
- Balanced Pressure and In-line balanced pressure proportioning systems.
- Bladder tank proportioner.
- Around the pump inductor.
- Handline nozzles with fixed induction/ pick-up tubes.

DISCHARGE DEVICES

- Foam chambers
- Air aspirating foam nozzles.
- Air aspirating and non air aspirating sprinkler heads and spray nozzles
- Foam makers for use with Floating Roof Storage Tanks/Bund protection system.

STORAGE/SHELF LIFE

When stored in the supplied packing and stored within the temperature range of 1.7°C - 49°C (35°F - 120°F) a shelf life of 20-25 years is expected. Freezing and thawing will have no impact on the performance.

For storing IFP UNILIGHT AR-AFFF TYPE 1/3, the following materials are recommended

SS-304, SS-316, Isophthalic Polyester Resin, Epoxy Resin, High Density Polyethylene.

Galvanized pipe and fittings must not be used in areas where undiluted concentrate will contact them since corrosion will result.

IFP UNILIGHT AR-AFFF TYPE 1/3^{C6}

COMPATIBILITY

IFP UNILIGHT AR-AFFF TYPE 1/3 is compatible with soft, hard, brakish or salt water. It can be used in combination with Dry powder extinguishing agents either separately or as twin agent systems.

IFP UNILIGHT AR-AFFF TYPE 1/3 shall not be mixed with other manufacturers foam concentrate except for use in emergency situations.

ENVIRONMENTAL AND TOXICOLOGICAL INFORMATION

IFP UNILIGHT AR-AFFF TYPE 1/3 is biodegradable, low toxicity and does not contain PFOS. However, as with any substance, care should be taken to prevent discharge from entering ground water, surface water, or storm drains. It can be treated in sewage treatment systems. Since facilities vary widely by location, disposal or discharge of IFP UNILIGHT AR-AFFF TYPE 1/3 concentrate or foam solution should be made in accordance with local government rules and regulations.

For further details see IFP UNILIGHT AR-AFFF TYPE 1/3 Material Safety Data Sheet.

STANDARDS

- UL 162
- ISO 7203-3
- EN 1568-3 & 4

STANDARD PACKING SPECIFICATION

Container Shape	Rectangular HM-HDPE	Rectangular HM-HDPE	Cylindrical HM-HDPE
Capacity	20 Ltrs	30 Lts	200 Lts.
Empty Weight	1.2 Kgs	1.8 kgs	9.0 kgs
Nominal Dimensions (mm)	H W B 357 282 278	H W B 495 242 380	H D 915 585

Container capacity and seaworthy packing also complied with customers' requirements

Contacts in Emergency : +919903914042

Integrated Fire Protection Pvt. Ltd.

60A, Pandit Madan Mohan Malabya Sarani, Kolkata - 700 020 INDIA
Phone : (91) (33) 2454-1061, 2475-5634, Fax : (91) (33) 2476-1107, 2283-1331
E-mail : integratedfire@gmail.com
www.integratedfire.net