INTEGRATED FIRE PROTECTIN PVT. LTD.

SELECTABLE GALLONAGE NOZZLE



Style 360, 361, 362

Style	Inlet Size	Length	Weigth Lbs(kg)	Flow Settings	
				GPM	LPM
360	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	5-10-24-40	19-37-90-150
361	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	13-25-40-60	50-100-150-230
362	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	12-23-30	50-90-115

Style 366

Style	Nozzle Pressure		Flow Settings		Actual Flow		Straight Stream Reach Effective		Straight Stream Reach Overall	
	PSI	BAR	GPM	LPM	GPM	LPM	Feet	Meters	Feet	Meters
366	75	5	30	115	26	98	67	20	90	27
			60	230	52	197	85	26	110	34
			90	360	82	310	99	30	130	39
			125	475	108	409	106	32	140	42
	100	7	30	115	30	115	78	24	95	29
			60	230	60	230	94	28	115	35
			90	360	90	360	109	33	135	41
			125	475	125	475	122	37	150	45
	125	8.5	30	115	34	129	81	25	100	30
			60	230	67	254	99	30	120	36
			90	360	107	401	115	35	135	41
			125	475	140	530	133	40	145	44



FM APPROVED

INTEGRATED FIRE PROTECTIN PVT. LTD.

Style 367

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
367	1-1/2" (38mm)	10.2" (259mm)	5.7 (2.6kg)	95-125-150-200	360-475-550-750

Style 368

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
368	2-1/2" (65mm)	11" (279mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950



Raised lug for flashover fog pattern



Newly improved handle with two reinforced pieces on each side to prevent breakage



Style 369

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
369	1-1/2" (38mm)	10.2" (259mm)	5.7 (2.6kg)	30-60-95-125-150-200	115-230-360-475-550-750

INTEGRATED FIRE PROTECTIN PVT. LTD.

MULTI-PURPOSE NOZZLE

Style 332

Style	Inlet Size	Length	Weight Lbs (kg)	Tip Options	Fog at 100 PSI	
					GPM	LPM
332	1-1/2" (38mm)	8.6" (218mm)	3.5 (1.6 kg)	3/8",1/2",5/8"	60	230

Style 333

Style	Inlet Size	Length	Weight Lbs (kg)	Tip Options	Fog at 100 PSI	
					GPM	LPM
333	1-1/2"or 2-1/2" (38mm or 65mm)	11" (280mm)	5.8 (2.6 kg)	3/4", 7/8" 15/16", 1"	135	510

Tip Size	Inlet Pressure (PSI)	Solid Bore Flow (GPM)	Fog Flow (GPM)	Combination Flow (GPM)
3/4"	50	115	95	199
	75	140	115	245
	100	160	135	285
7/8"	50	155	95	232
	75	195	115	295
	100	220	135	340
15/16"	50	180	95	250
	75	195	115	300
	100	250	135	365
1"	50	205	95	270
	75	240	115	340
	100	285	135	385

NFPA1964
COMPLIANT



INTEGRATED FIRE PROTECTIN PVT. LTD.

AUTOMATIC NOZZLE

Style 311, 312, 314, 314-TP

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
311	1-1/2" (38mm)	9.2" (234mm)	3.7 (1.7)	60-125	230-475
312	1-1/2" (38mm)	10.6" (269mm)	5.6 (2.5)	60-200	230-750
314	2-1/2" (65mm)	12.2" (309mm)	8 (3.6)	75-325	285-1325
314-TP	2-1/2" (65mm)	17.1" (435mm)	9.9 (4.5)	75-325	285-1325



Style 321



Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
321	1" (25mm)	8.6" (220mm)	3.1 (1.4kg)	10-125	40-475

Style 322, 322-SP



Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
322	1-1/2"(38mm)	9.0" (230mm)	3.2 (1.4kg)	10-125	40-475
322-SP	1-1/2"(38mm)	9.0" (230mm)	3.2 (1.4kg)	10-125	40-475

INTEGRATED FIRE PROTECTIN PVT. LTD.

HIGH PRESSURE NOZZLE

Style 302

Style	Inlet Size	Length	Weight Lbs (kg)	Flow Settings	
				GPM	LPM
302	1" (25mm)	19.7" (500mm)	4.6 (2.1kg)	5-10-24-40@100psi	19-37-90-150@7bar



Style 305

Style	Inlet Size	Length	Weight Lbs.(kg)	Flow Settings @145 psi	
				GPM	LPM
305	1" (25 mm)	16" (406 mm)	5.5 (2.5 kg)	17 or 30	65 or 115

